

## Flooring

### CompactFloor® LIQUID

Process CompactFloor® LIQUID according to the installation instructions. Allow CompactFloor® LIQUID to cure completely, carry out the heating protocol and keep the surface dust-free. Approved adhesives must be processed in accordance with Mapei application technology.

Parquet / Laminate	8 mm mosaic block / herringbone		8 mm solid english bond straight / ladder pattern	
	2- or 3-layer ready-made parquet parquet plank / country style single plank		2- or 3-layer ready-made parquet short format less than 100 cm	
	22 mm on-edge lamel parquet		22 mm strip parquet and solid parquet up to 2,70 m	
	Laminate (Manufacturer release for full-surface bonding required)			
Tiles / Natural stone	Ceramic tiles / Porcelain stoneware Tile size: max. 60 x 60 cm Aspect ratio: 1:1 to 3:1 Minimum thickness: 9 mm Breaking strength: min. 1.500 N Technical joint width: min. 3 mm		Natural stones Tile size: max. 60 x 60 cm Aspect ratio: 1:1 to 3:1 Minimum thickness: 15 mm Breaking strength: min. 1.500 N Technical joint width: min. 3 mm	
Textile / Elastic floor coverings	Textile coverings		PVC / CV coverings design coverings	
			Needle punched flooring	